REV-A-SHELF® Wood Classics™

Full Circle Lazy Susan

INSTALLATION INSTRUCTIONS
For 4WLS072 and 4WLS073



INSTALLATION INSTRUCTIONS

1. Insert shelf support in tray from bottom with keyway to rear of tray and position top shelf hub on top of tray with keyway to rear of tray. Install three (3) 3/4" x #8 (M1812-251-2) self tapping pan head screws through top hub into shelf support and tighten.
2. Locate screw holes with template provided to install bottom positioner on cabinet floor with four (4) each 3/4" by 8 oval head screws.
3. Locate screw holes with template provided to install upper pivot support with four (4) each 3/4" by 8 truss head screws.
4. Insert bottom end of shaft thru upper shelf and assemble collar. Repeat for bottom shelf and temporarily tighten collar 6-10 inches from the bottom end of the shaft.

   Note: If desired, the lower collar may be discarded to reduce the height of the lower shelf in the finished installation.
5. Tilt the shaft to a horizontal position and ease the shelves thru the cabinet opening. Raise the shaft to an upright position and engage the lower end in the bottom positioner. Engage and seat the upper shaft assembly in the upper pivot support. Tighten the shaft locking screw and the locking screw in the bottom positioner.
6. Space the shelves as desired and tighten the collar(s) with the locking screws.

REV-A-SHELF®
Your Worldwide Accessory Source!
STORAGE ORGANIZING

2409 Plantside Drive • Jeffersontown, KY 40299
800-626-1126 • FAX 502-491-2215